

PoolDose Double

Offering the fullest range of measurements alongside user-friendly operation, PoolDose Double combines two peristaltic dosing pumps, multi-measurement capability and automatic proportional dosing to deliver the ideal solution for above-ground, indoor and outdoor pools.

Parameters

A pH (0 – 14) and ORP (0 – 1,000 mV)

B pH (0 – 14), ORP (0 – 1,000 mV) and Free Chlorine (0 – 5 ppm)

Flow Rate and Pressure

A Flow rate 0.4 l/h ; Pressure 1.5 bar

B Flow rate 1.5 l/h ; Pressure 1.5 bar

Pool Size

A Indoor 1 – 25 m³ ; Outdoor 1 – 20 m³

B Indoor 5 – 130 m³ ; Outdoor 5 – 110 m³

IP65 Enclosure

Dimensions 205 x 194 x 133 mm (LxHxD)

Material ABS

Main Board

Alphanumeric display 16 characters x 2 lines

Power supply 220 Vac, 50/60Hz



Features

New: Easily connect device to the app by scanning a QR code

New: Wi-Fi module enables pool management via app

New: Galvanized electrical and measure insulation

New: Three PVDF rollers and Santoprene tubing

New: PoolDose Double manages the Chlorine Generator thanks to internal relay

New: Water meter flow rate input totalizes swimming pool water changes

Amperometric probe include high-grade insulation

Probe holder with amperometric chlorine probe included in PoolDose Double pH, ORP and CL versions

Installation kit included

Multi-language menu

Wizard Probe Calibration and Degree of Health

No technical skill required

Circulation pump checks "Power On" flow trigger

Input temperature probe range 0 - 50°C for measure compensation only

Input level probe checks product levels

Extra dosing available thanks to pH and chlorine relay

Proportional dosing TWM (time width modulation) mode

PoolDose Double working with Chlorine Generator device

