

FELIX ENERGY

Inversor Hibrido ON / OFF Grid 11000W



Product parameters

Capacity	11KVA/11KW
Maximum PV input Power	11KW
Parallel Capability	NO
Lithium Battery Activation	YES (By PV or Utility)
Lithium Battery Communication	YES(RS485)
Built-in WIFI	Optional
AC INPUT	
Nominal Voltage	230VAC
Acceptable Voltage Range	170-280VAC(For personal Computer) 90-280VAC(For Home Appliances)
Frequency	50/60 Hz (Auto sensing)
AC OUTPUT	
Nominal Voltage	220/230/240VAC
Surge Power	22000VA
Frequency	50/60 Hz
Waveform	Pure Sine wave
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)
Peak Efficiency	94%
Overload Protection	5s@>=140% load; 10s@110%~140% load
Admissible Power Factor	0.6~1 (inductive or capacitive)
BATTERY	
Battery Voltage	48VDC
Maximum Discharge Current	220A
Floating Charge Voltage	54VDC
OverCharge Protection	63VDC
Charging Method	CC/CV
SOLAR CHARGER & AC CHARGER	
Solar Charger TYPE	MPPT
Max.PV Array Power	5500W*2
Max. PV Array Open Circuit Voltage	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC
Max. Solar Input Current	18A*2
Max. Solar Charge Current	160A
Max. AC Charge Current	120A
Max. Charge Current	160A
PHYSICAL	
Dimensions,DxWxH(mm)	540*403*122
Net Weight (Kgs)	14.8
Communication Interface	RS232/RS485/DRY CONTACT
LCD	YES
ENVIRONMENT	
Operating Temperature Range	-10°C~50°C
Storage temperature	-15°C~60°C
Humidity	5% to 95% Relative Humidity (Non-condensing)